

Tabla #25

18x7, 19x7

Clase 18x7

Alma de fibra
Alma de acero



Resistente a la rotación

18x7 Class

Fiber core
Steel core

Rotation resistant ropes

ELEFANTE®
negro
bright



Diámetro		18x7 Alma de fibra		19x7 Alma de acero		Resistencia a la Ruptura			
Diameter		Approximate Weight		Approximate Weight		Minimum Breaking Force			
Pulgadas Inch	Milímetros mm	lb / ft	kg / m	lb / ft	kg / m	Arado Mejorado / IPS lb	Ton*	Arado Extra Mejorado / EIP lb	Ton*
3/8	9.5	0.24	0.36	0.26	0.39	11,155	5.06	12,260	5.56
7/16	11.11	0.33	0.49	0.35	0.52	15,145	6.87	16,600	7.53
1/2	13	0.43	0.64	0.45	0.67	19,700	8.9	21,600	9.8
9/16	14.5	0.55	0.82	0.58	0.86	24,800	11.2	27,200	12.3
5/8	16	0.68	1.01	0.71	1.06	30,600	13.9	33,600	15.2
3/4	19	0.97	1.44	1.02	1.52	43,600	19.8	48,000	21.8
7/8	22	1.32	1.96	1.39	2.07	59,000	26.8	65,000	29.5
1	26	1.73	2.57	1.82	2.71	76,600	34.7	84,400	38.3
1-1/8	29	2.19	3.26	2.30	3.42	96,400	43.7	106,200	48.2
1-1/4	32	2.70	4.02	2.84	4.23	118,400	53.7	130,200	59.1
1-3/8	35	3.27	4.87	3.43	5.10	142,600	64.7	156,800	71.1
1-1/2	38	3.89	5.79	4.08	6.07	168,800	76.6	185,600	84.2

Normas de Referencia: ASTM-A-1023; API Spec 9A; EN 12385-4 //
Reference specifications: ASTM-A-1023; API Spec 9A; EN 12385-4

*Toneladas Métricas // Metric tonnes