

Estrobo de tres brazos

Modelo "C"

Diámetro de Cable pulg.	EIPS Capacidades en Toneladas de Angulo Horizontal			Crosby A-342 una Aleación de Enlace Maestro			Crosby G-2130 Grillete Tamaño Nominal pulg.	Longitud Mínima
	60°	45°	30°	Diámetro pulg.	W" X L" (pulg.)			
1/4"	1.69	1.38	0.98	1/2"	2.5"	5"	3/8"	1'-3"
3/8"	3.6	3.0	2.1	3/4"	2.75"	5.5"	1/2"	1'-8"
1/2"	6.5	5.3	3.8	1"	3.5"	7"	5/8"	2'
5/8"	10.1	8.3	5.9	1"	3.5"	7"	3/4"	2'-4"
3/4"	14.5	11.9	8.4	1-1/4"	4.38"	8.75"	7/8"	2'-9"
7/8"	19.7	16.1	11.4	1-1/4"	5.25"	10.5"	1"	3'-3"
1"	25.5	20.8	14.7	1-3/4"	6"	12"	1-1/8"	3'-6"
1-1/8"	31	25	18.0	2"	7"	14"	1-1/4"	4'
1-1/4"	39	32	23.0	2-1/4"	8"	16"	1-3/8"	4'-6"
1-3/8"	47	38	27.0	2-1/4"	8"	16"	1-1/2"	5'
1-1/2"	55	45	32.0	2-3/4"	9.5"	16"	1-1/3"	5'-6"
1-3/4"	73	59	42.0	2-3/4"	9.5"	16"	2"	6'-6"
2"	96	78	56.0	3-1/4"	10"	20"	2-1/2"	8'
2-1/4"	114	93	66.0	4"	10"	20"	2-1/2"	8'-9"



ESTROBOS

Estrobo de cuatro brazos

Modelo "D"

Diámetro de Cable pulg.	EIPS Capacidades en Toneladas de Angulo Horizontal			Crosby A-342 una Aleación de Enlace Maestro			Crosby G-2130 Grillete Tamaño Nominal pulg.	Longitud Mínima
	60°	45°	30°	Diámetro pulg.	W" X L" (pulg.)			
1/4"	2.25	1.84	1.3	5/8"	3"	6"	3/8"	1'-3"
3/8"	4.8	4	2.8	1"	3.5"	7"	1/2"	1'-8"
1/2"	8.7	7.1	5.0	1-1/4"	4.38"	8.75"	5/8"	2'
5/8"	13.5	11	7.8	1-1/2"	5.25"	10.5"	3/4"	2'-4"
3/4"	19.4	15.8	11.2	1-1/2"	5.25"	10.5"	7/8"	2'-9"
7/8"	26.3	21.5	15.2	1-3/4"	6"	12"	1"	3'-3"
1"	33.9	27.7	19.6	2"	7"	14"	1-1/8"	3'-6"
1-1/8"	41.5	33.9	24.0	2-3/4"	9.5"	16"	1-1/4"	4'
1-1/4"	52	42	30.0	2-3/4"	9.5"	16"	1-3/8"	4'-6"
1-3/8"	62	51	36.0	3-1/2"	12"	24"	1-1/2"	5'
1-1/2"	73	59	42.0	3-1/2"	12"	24"	1-1/3"	5'-6"
1-3/4"	97	79	56.0	3"	9"	18"	2"	6'-6"
2"	128	105	74.0	3-3/4"	10"	20"	2-1/2"	8'
2-1/4"	152	124	88.0	4"	10"	20"	2-1/2"	8'-9"

